Homelift Selector Sheet



Salesperson:	Filled O	ut	Checked by:	Sheet No:		Quote Ref No:		
Site Address:								
Site Address.								
Telephone No:								
Date Form Complete: 14/08/2000 Due to C			o Client by:	lient by: Send D			Direct: Yes	
Quotation to:								
Contact: Telephon			hone No:	No: Facsimile No:				
		*						
No. of Units:	No. of Units: Type of Contract: Stannah							
Fixed Price to: 6 month				2.5%				
Travel: mm	avel: mm Cabin Handing					Building Work: By Us		
Headroom: m								
Project Funder: LA/Council						Any Special Requ	uirements:	
Pricing: LA/HA								
Survey: Required								
Installation Date:								
	Ont	ions Required			Included	Extra	Price	
Builders	Builders Work						11100	
Service	Visits - 2 Per Y	ear					£99	
Telephone							£68	
Fold Down Padded Seat and Grab Rails							£134	
Grab Rails							£35	
	Additional Set of Car Switches						£97	
		und During Lift					£150	
		Mounted to Wa		ret floor			£45 £95	
	Keyswitch to Isolate Landing Pushes at Ground and First floor Comprehensive Service Contract - 2 visits per year						£404	
Rear Gu	isits per year				£110			
							<u> </u>	
		eputation No						
Customer Type	Private							
Building Type		Private House						
New/Existing Buildin		ıg						
Major Customer	No							
Job Grading	A							

Salesman: Job No:

Date: 14/08/2000



HOMELIFT SALES/SITE SURVEY CHECKLIST		\square
GROUND FLOOR		
Floor to ceiling height mm (To be measured at the lift guide position)		
Space between ceiling and first floor mm		
FIRST FLOOR		
Floor to ceiling height mm		
Wall construction		
Floor construction		
Type of floor covering to gantry board (e.g. carpet, floor boards etc.)		
Support wall aligns on both floors Yes		
	Yes	No
Check List: Position of Pump Unit shown on drawings		
Hydraulic hose length required mm		
Type of wheelchair: Name Length mm	Width	mm
Clients Disability		
Ensure adequate space for relocation of furniture etc. Ensure the lift door is hinged to suit the customers needs. Ensure the location of the lift will accommodate the fixing of the top beam to for advice if in doubt) Remember that a gap larger than 75mm behind the guides must be guarded. Notify customers builders of electrical requirements.	the rear wa	all. (Ring
<u>COMMENTS:</u>		