



LOOM DETAILS
 LOOM 'A' = TOP CALL
 LOOM 'B' = BOTTOM CALL
 LOOM 'C' = TOP LOCK
 LOOM 'D' = BOTTOM LOCK
 LOOM 'E' = CARRIAGE
 LOOM 'F' = GUIDE

EXAMPLES:
 C4 = LOOM 'C'
 (TOP LOCK) WIRE No.4
 'E'R = LOOM 'E'
 (CARRIAGE) RED WIRE

PANEL DATA
 CONTACTORS 24V d.c. COIL
 UPC MAIN
 N/O: 1/2, 3/4, 5/6
 N/C: 21/22
 COIL A1 A2

RELAYS 24V d.c. COLIS
 TC, LC, UR, DR, DN, URDR
 N/O: 5/9, 6/10, 7/11, 8/12
 N/C: 1/9, 2/10, 3/11, 4/12
 COIL 13-14

TIMERS 24V d.c. COILS
 CCT, ACT, LDT, JT
 N/O: 5/9, 6/10, 7/11, 8/12
 N/C: 1/9, 2/10, 3/11, 4/12
 COIL 13-14

Wiring Schematic, Midlift PX iss 09.10.03 (standard swing doors, constant pressure controls) ref. 0230.8010 D